





Switchvox SOHO and SMB Specification Chart

				
	Switchvox SOHO AA60 Appliance with 10 Silver Subscriptions	Switchvox SMB AA60 Appliance with 10 Silver Subscriptions	Switchvox SMB AA300 Appliance with 10 Silver Subscriptions	Switchvox SMB AAA350 Appliance with 10 Silver Subscriptions
Switchvox Bundles				
Ideal For:	Demanding small offices or home offices that need a professional phone system.	Offices that don't have a computer rack and need the space-savings of a small platform.	Medium-sized businesses with a computer rack or shelf space that want the power of a server-class PBX.	Medium to large businesses that want a high performance, highly redundant, full featured rackmount PBX.
Users / Calls:	- Supports 1 to 20 users - Up to 10 concurrent calls	- Supports 1 to 30 users - Up to 12 concurrent calls	- Supports 1 to 150 users - Up to 45 concurrent calls	- Supports 1 to 400 users - Up to 75 concurrent calls
Recording / Conferencing:	None Available	- Up to 5 concurrent recorded calls - Up to 5 simultaneous conference users	- Up to 10 concurrent recorded calls - Up to 15 simultaneous conference users	- Up to 20 concurrent recorded calls - Up to 30 simultaneous conference users
Redundancy / Failover:	Cold Spare Available	Cold Spare Available	Cold Spare Available	- RAID Controller with mirrored drives - Redundant Power Supplies - Cold Spare Available
Subscription Options:	Silver Subscription Plan	- Silver Subscription Plan - Gold Subscription Plan - Platinum Subscription Plan	- Silver Subscription Plan - Gold Subscription Plan - Platinum Subscription Plan	- Silver Subscription Plan - Gold Subscription Plan - Platinum Subscription Plan
Warranty Options:	- Standard 1 Year Warranty - 3 Year Extended Warranty	- Standard 1 Year Warranty - 3 Year Extended Warranty	- Standard 1 Year Warranty - 3 Year Extended Warranty	- Standard 1 Year Warranty - 3 Year Extended Warranty
Switchvox Hardware Specifications				
Form Factor:	Desktop/Wallmount	Desktop/Wallmount	Desktop/Rackmount	Redundant Rackmount
Weight:	10 lbs	10 lbs	30 lbs (40 lbs with optional rails)	47 lbs (57 lbs with optional rails)
Power Supply:	Single 85W	Single 85W	Single 300W	Dual Redundant 500W
Dimensions:	10.5"x12.5"x3.5" (DxWxH)	10.5"x12.5"x3.5" (DxWxH)	15.25"x19"x5.25" (DxWxH)	25.6"x19"x5.25" (DxWxH)
Fans:	1x60mm side fan	1x60mm side fan	2x60mm rear fans	3x80mm mid fans 2x60mm rear fans
Number of Add-on Boards:	Two	Two	Three	Three
Add-on Boards Supported:	TDM410, TDM800, TE122 (only one TE122 supported)	TDM410, TDM800, TE122 (only one TE122 supported)	TDM410, TDM800, TDM2400, TE122, TE205/207, TE405/407	TDM410, TDM800, TDM2400, TE122, TE205/207, TE405/407
Processor:	Intel Celeron Processor + ~1.2GHz, 533MHz FSB	Intel Celeron Processor + ~1.2GHz, 533MHz FSB	Intel CPU Pentium Dual-Core ~1.6GHz, 800MHz FSB	Intel Core 2 DUO CPU ~2.40GHz, 1066Mhz FSB
RAM:	1 Stick of 512Mb DDR2 533MHz, Non-ECC	1 Stick of 512Mb DDR2 533MHz, Non-ECC	1 Stick of 1Gb DDR2 533MHz, Non-ECC	2 Sticks of 1Gb DDR2 533MHz, Non-ECC
Hard Drive:	SATA 80 Gb Drive +5400 rpm	SATA 80 Gb Drive +5400 rpm	SATA 80 Gb Drive +7200 rpm	Dual SATA 80 Gb Drive +7200 rpm
Raid Card:	None Available	None Available	None Available	Adaptec SATA RAID Controller +RAID 1 configuration
Hot Swap Canister:	None Available	None Available	None Available	Hot-Swappable SATA Enclosure